



**PT. SMART CAKRAWALA AVIATION**

**WORK ORDER**

**Form: SCA/MTC/030**

Subject :	No.	WO/070-PK-SNX/VI/2023
<b>Perform CASR Inspection</b>	Date	22-Jun-2023
	A/C Reg.	PK-SNX EC130T2-8829
Reference :	Prepared By	TS
MP EC130T2 Issued 01, Rev. 00	Checked By	CI
	Approved By	TM
	To : Engineer In Charge	

**Description :**

1. Perform CASR inspection EC130T2
2. Make an entry in Maintenance Log.
3. Return the Completed Work Order and Form to PPC.

#If any finding, please close the routine card, and transferred to inspection card.

**Additional Work :**

Compliance Statement	Sign & Date Company Lic. No.:  (Engineer In Charge)	Signature  (Technical Manager)
----------------------	--	--------------------------------------

**AIRCRAFT CHECK WORK SUMMARY**  
**(Form: SCA/MTC/051)**

DATE OF ISSUED	JO/WO #	TYPE OF MAINTENANCE	DATE OF ACCOMPLISHED
22 Jun 2023	WO/070-PK-SNX/VII/2023	CASR Inspection	

A/C Type	Mfg. Serial Number	A/C Registration
EC130T2	8829	PK-SNX

**AIRCRAFT DATA**

Subject	Pos #	Serial Number (SN)	TTSN/TCSN
Engine	#1	53467	
	#2	-	
Propeller/Rotor	#1		
	#2	-	
Landing Gear	NLG		
	LH MLG		
	RH MLG		

**PACKAGE COVERED**

No	Subject	Qty	Remark
1	Non-Routine Card	4	
2	Inspection Card	-	
3	Work Order	1	
4	Summary Inspection List	1	
5	Material and Tool List	-	
6	Escalation form	-	
7	CRS (SMI / Unscheduled Maintenance)	1	

**INSPECTION CARD (IC) LIST (Finding during maintenance)**

No	Taskcard Ref	Subject	Status		Name/ Sign & Stamp
			Open	Close	
IC-001					
IC-002					
IC-003					
IC-004					
IC-005					
IC-006					

<u>IC-007</u>					
<u>IC-008</u>					
<u>IC-009</u>					
<u>IC-010</u>					
<u>IC-011</u>					
<u>IC-012</u>					
<u>IC-013</u>					
<u>IC-014</u>					
<u>IC-015</u>					

Prepared by :  
Technical Support



Hani

Checked by :  
Chief Maintenance



Dodit

Verified by :  
Chief Inspector



Yanuar

Approved by :  
Technical Manager



Istiono



**SUMMARY INSPECTION ITEMS**  
**(Form: SCA/MTC/050)**

WO Ref: WO/070-PK-SNX/VI/2023

NO.	TASK CARD NO.	DESCRIPTION	DATE	EST MHR	NAME	STAMP
3	NRC001	PITOT STATIC				
4	NRC002	TRANSPOUNDER TEST				
5	NRC003	ALTIMETER TEST				
6	NRC004	ELT TEST				



**INSPECTION CARD**  
(Form: SCA/MTC/ 048)

TECHNICAL  
DEPARTMENT

1. CARD #	2. JO/WO #	3. ORIGINATOR	4. CARD REF	5. DATE
6. A/C REG/MSN	7. A/C TYPE	8. TRADE	12. VENDOR ORDER #	
9. ZONE	10. STA	11. MTC TYPE		

13. DESCRIPTION/DEFECT-IF FINDING OF CPCP INSPECTION, PLEASE COMPLETE SET. 20	14 PPC/ENG	15 DATE

16. CORRECTIVE ACTION	17 MECH	18 ENG. LIC	19 DATE
Performed at A/C TT : ..... A/C TC /LDG : .....			
20. CORROSION INFORMATION			
LOCATION  CORROSION <input type="checkbox"/> Isolated <input type="checkbox"/> Widespread CORROSION LVL <input type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 PROPOSED ACTION <input type="checkbox"/> Doublers <input type="checkbox"/> Others .....	CAUSE OF DAMAGE <input type="checkbox"/> Environment <input type="checkbox"/> Internal Leakage <input type="checkbox"/> Chemical Spill <input type="checkbox"/> LAV/Galley Spill <input type="checkbox"/> Blocked Drain <input type="checkbox"/> Wet Insulation Blanket <input type="checkbox"/> Other		
21. If the defect is RII, Please Sign this card finally by RII Inspector	INSP	DATE	
NOTICE OF INSPECTOR			

22. PARTS REQUIRED						
PART DESCRIPTION	PART NO	QTY	SERIAL NO		STATUS	
			ON	OFF	CLOSE	OPEN
23. TOOLS REQUIRED						
DESCRIPTION	PART NO. / MODEL		NEXT CALIBRATION DATE	STATUS		



PT. SMART CAKRAWALA AVIATION

# CERTIFICATE RETURN TO SERVICE

## SCHEDULED MAINTENANCE INSPECTION

### (CRS-SMI)

A/C TYPE	EC 130 T2	TTSN	:
A/C REG	PK-SNX	TCSN	:
MSN	8829	DATE	:
TYPE OF INSPECTION	CASR INSPECTION		
DUE AT	:		
REFF	MP EC130T2 Issued 01, Rev. 00		
EXCEPTION			
AUTHORIZED PERSON			
I hereby certify that this aircraft has been maintained accordance with CASR and Maintenance Program.			
Aircraft safe and airworthy for flight			
NAME	CAT	AMEL/OTR NO	SIGN&STAMP
	AIRFRAME & POWER PLANT		
	EIRA		
THE NEXT DUE TYPE OF INSPECTION :			
DUE AT :			



**NON ROUTINE CARD**  
**(Form: SCA/MTC/047)**

1. JO/WO #	2. DATE	3. MTC TYPE	4. A/C REG/MSN
WO/070-PK-SNX/VI/2023		FUNCTIONAL CHECK	PK-SNX
5. CARD #	6. ATA SPEC	7. TRADE	8. STA
#001	34		
9. ZONE	10. PANEL		

11. DESCRIPTION

**PERFORM PITOT STATIC FUNCTIONAL TEST AIRCRAFT**

REFERENCE	<input checked="" type="checkbox"/> AMM Ch. 34-10-00	<input type="checkbox"/> EMM Ch	<input type="checkbox"/> OTHER
RII (*)	<input type="checkbox"/> Y	<input checked="" type="checkbox"/> N	MHR :

12. RESULT				MECH	ENG	INSP (*)
Performed at A/C TT : ..... A/C TC /LDG : .....						
FINDING	<input type="checkbox"/> Y	<input type="checkbox"/> N	ACT MHR :	DATE/TIME (DD/MM/YY)		
INSPECTION CARD (IC) #						

13. PARTS REQUIRED

DESCRIPTION	PART NO	QTY	REMARK	
			STOCK	STATUS

14. TOOLS REQUIRED

DESCRIPTION	PART NO / MODEL	NEXT CALIBRATION DATE	STATUS



**NON ROUTINE CARD**  
**(Form: SCA/MTC/047)**

1. JO/WO #	2. DATE	3. MTC TYPE	4. A/C REG/MSN
WO/070-PK-SNX/VI/2023		FUNCTIONAL CHECK	PK-SNX
5. CARD #	6. ATA SPEC	7. TRADE	8. STA
#002	34		
9. ZONE	10. PANEL		

11. DESCRIPTION

**PERFORM TRANSPONDER FUNCTIONAL TEST AIRCRAFT**

REFERENCE	<input checked="" type="checkbox"/> AMM Ch. 34-51-37	<input type="checkbox"/> EMM Ch	<input type="checkbox"/> OTHER
RII (*)	<input type="checkbox"/> Y	<input checked="" type="checkbox"/> N	MHR :

12. RESULT				MECH	ENG	INSP (*)
Performed at A/C TT : ..... A/C TC /LDG : .....						
FINDING	<input type="checkbox"/> Y	<input type="checkbox"/> N	ACT MHR :	DATE/TIME (DD/MM/YY)		
INSPECTION CARD (IC) #						

13. PARTS REQUIRED

DESCRIPTION	PART NO	QTY	REMARK	
			STOCK	STATUS

14. TOOLS REQUIRED

DESCRIPTION	PART NO / MODEL	NEXT CALIBRATION DATE	STATUS



**NON ROUTINE CARD**  
**(Form: SCA/MTC/047)**

1. JO/WO #	2. DATE	3. MTC TYPE	4. A/C REG/MSN
WO/070-PK-SNX/VI/2023		FUNCTIONAL CHECK	PK-SNX
5. CARD #	6. ATA SPEC	7. TRADE	8. STA
#003	34		
9. ZONE	10. PANEL		

11. DESCRIPTION

**PERFORM ALTIMETER FUNCTIONAL TEST AIRCRAFT**

REFERENCE	<input checked="" type="checkbox"/> AMM Ch. 34-12-00,5-1	<input type="checkbox"/> EMM Ch	<input type="checkbox"/> OTHER
RII (*)	<input type="checkbox"/> Y	<input checked="" type="checkbox"/> N	MHR :

12. RESULT				MECH	ENG	INSP (*)
Performed at A/C TT : ..... A/C TC /LDG : .....						
FINDING	<input type="checkbox"/> Y	<input type="checkbox"/> N	ACT MHR :	DATE/TIME (DD/MM/YY)		
INSPECTION CARD (IC) #						

13. PARTS REQUIRED

DESCRIPTION	PART NO	QTY	REMARK	
			STOCK	STATUS

14. TOOLS REQUIRED

DESCRIPTION	PART NO / MODEL	NEXT CALIBRATION DATE	STATUS



**NON ROUTINE CARD**  
**(Form: SCA/MTC/047)**

1. JO/WO #	2. DATE	3. MTC TYPE	4. A/C REG/MSN
WO/070-PK-SNX/VI/2023		FUNCTIONAL CHECK	PK-SNX
5. CARD #	6. ATA SPEC	7. TRADE	8. STA
#004	25		
9. ZONE	10. PANEL		

11. DESCRIPTION

**PERFORM ELT FUNCTIONAL TEST AIRCRAFT**

REFERENCE	<input checked="" type="checkbox"/> AMM Ch. 25-66-01	<input type="checkbox"/> EMM Ch	<input type="checkbox"/> OTHER
RII (*)	<input type="checkbox"/> Y	<input checked="" type="checkbox"/> N	MHR :

12. RESULT				MECH	ENG	INSP (*)
Performed at A/C TT : ..... A/C TC /LDG : .....						
FINDING	<input type="checkbox"/> Y	<input type="checkbox"/> N	ACT MHR :	DATE/TIME (DD/MM/YY)		
INSPECTION CARD (IC) #						

13. PARTS REQUIRED

DESCRIPTION	PART NO	QTY	REMARK	
			STOCK	STATUS

14. TOOLS REQUIRED

DESCRIPTION	PART NO / MODEL	NEXT CALIBRATION DATE	STATUS



Aircraft Registration: **PK-SNX**

WO# Nr: WO/070-PK-SNX/VI/2023

# **Additional Work Sheet**

## **CASR Inspection**

## Parts Used Sheet

## Special Tool Used



Aircraft Registration: **PK-SNX**

WO# Nr: **WO/070-PK-SNX/VI/2023**

# **Additional Work Sheet**

## **CASR Inspection**

## Parts Used Sheet

## Part Used



## **Additional Work Sheet CASR Inspection**

Aircraft Registration: **PK-SNX**

WO# Nr: **WO/070-PK-SNX/VI/2023**

## Parts Used Sheet

## Part Used

	<b><u>ATC Transponder Inspection</u></b> <u>Instructions</u>
	<ul style="list-style-type: none"> <li>- Each Listed Inspection Item is to be performed in accordance with the AMM and any other applicable publications</li> <li>- Portable test Equipment is to be calibrated every 24 months</li> <li>- Reference CASR Part 43 Appendix F</li> </ul>

Aircraft Registration :	PK -	TTIS:	
Aircraft Type :		TCIS:	
Aircraft Serial Number :		DATE:	
Test Equipment PN:		Portable test Equipment is to be calibrated every 24 months	
Test Equipment SN:		Due Calibration:	
Transponder PN:		Transponder SN:	

No.	TASK	<b>SIGNATURE</b>	
		<b>SIGN</b>	<b>STAMP</b>
1	<b>RADIO Reply Frequency</b> <ul style="list-style-type: none"> <li>a) For all classes of ATCRBS Transponder interrogate the transponder and verify the reply frequency is 1090 + 3 MHz</li> <li>b) For classes 1A, 2A, 3A and 4 Mode S Transponders interrogate the transponder and verify the reply frequency 1090 + 1 MHz</li> </ul>		
2	<b>SUPPRESSION</b> <p>When classes 1A and 2A ATCRBS Transponders, are interrogated at a rate between 230 and 1200 mode ¾ interrogation per second :</p> <ul style="list-style-type: none"> <li>a) Verify that it does not respond to more than 1% of ATCRBS interrogations when the amplitude of P2 pulse is equal to the P1 Pulse.</li> <li>b) Verify that Transponder replies to at least 90% of ATCRBS interrogations when the amplitude of the P2 pulse is 9dB less than the P1 pulse. If the test is conducted with a radiated test signal, the interrogator rate shall be 235 +5 interrogations per second unless a higher rate has been approved for the test equipment used in that location.</li> </ul>		

3	<p><b>SENSITIVITY</b></p> <p>a) Verify that for any class of ATCRBS Transponder, the receiver minimum trigger level (MTL) of the System is 73 + 3 dbm, or that for any class of Mode S transponder the receiver MTL for mode S format (P6 type) interrogations is 74 +3 dbm by use of a test set:</p> <ul style="list-style-type: none"> <li>i) Connected to the antenna end of the transmission line (shop).</li> <li>ii) Connected to the antenna terminal of the transponder with correction for transmission line loss, or (shop).</li> <li>iii) Utilizing a radiated signal (Field).</li> </ul> <p>b) Verify that the difference in mode 3/A and Mode C receiver sensitivity does not exceed, 1 db for either any class of ATCRBS transponder or any class of Mode S Transponder.</p>		
4	<p><b>VERIFY FREQUENCY (RF) PEAK OUTPUT POWER:</b></p> <p>a) Verify that the transponder RF output power is within specifications for the class of transponder. Use the same conditions as described in 3 a) (i), (ii), and (iii) above.</p> <p>b) For class 1A and 2A ATCRBS Transponders, verify that the minimum RF peak output power is at least 21.0 dbw (125 watts).</p> <p>c) For class 1A, 2A, 3A and 4 and those classes 1B, 2B, and 3B Mode S Transponders that include the optional high RF peak output power, verify the minimum RF peak output power is at least 21.0 dbw (125 watts).</p> <p>d) For any class of ATCRBS or any class of Mode S Transponder, verify that the maximum RF peak output power does not exceed 27.0 dbw (500 watts).</p>		
*** End of ATC Transponder Test Items ***			

#### **RETURN TO SERVICE**

The work recorded above has been carried out in accordance with the requirements of the Civil Aviation Safety Regulation for the time being in force and in that respect the aircraft is consider fit for Release to Service.

Name : \_\_\_\_\_ Place/Date : \_\_\_\_\_

Sign & Stamp : \_\_\_\_\_ : \_\_\_\_\_

	<p style="text-align: center;"><b>Static Pressure Inspection Instructions</b></p> <ul style="list-style-type: none"> <li>- Each Listed Inspection Item is to be performed in accordance with the AMM and any other applicable publications</li> <li>- Portable test Equipment is to be calibrated every 24 months</li> <li>- Reference CASR Part 43 Appendix E</li> </ul>
---	---

Aircraft Registration :	PK -	TTIS:	
Aircraft Type :		TCIS:	
Aircraft Serial Number :		DATE:	
Test Equipment PN:		Portable test Equipment is to be calibrated every 24 months	
Test Equipment SN:		Due Calibration:	
Altimeter PN:		Altimeter SN:	

NO.	TASK	SIGNATURE	
		SIGN	STAMP
1	<p><b>STATIC PRESSURE SYSTEM</b></p> <ul style="list-style-type: none"> <li>a) Ensure freedom from entrapped moisture and restrictions.</li> <li>b) Determine that leakage is within the tolerances established in part 23 Section 23.1325 or part 25 sections 25.1325 whichever is applicable.</li> <li>c) Check that the static port heater is operative (if installed).</li> <li>d) Ensure that no alterations or deformations of the airframe surface have been made that would affect the relationship between air pressure in the static pressure system and true ambient static air pressure for any flight condition.</li> </ul>		
2	<p><b>ALTIMETER</b></p> <p><u>Scale Error</u></p> <ul style="list-style-type: none"> <li>a) With the barometric scale at 29.92 in Hg, the altimeter shall be subjected successively to pressure corresponding to the altitude specified in the Table I, up to the maximum normally expected operating altitude of the airplane in which the altimeter is to be installed .e.g. Cessna Caravan 208B is certified to a maximum altitude of 24.000 feet. The reduction in pressure shall be at a rate not in excess of 20.000 ft. per minute to within approximately 2000 ft. of the test point. The test point shall be approached at a rate compatible with the test equipment. The altimeter shall be kept at a pressure corresponding to each test point for at least 1 minute, but not more than 10 minutes, before a reading is taken the error at all test points must not exceed the tolerances specified in Table I.</li> </ul>		

NO.	TASK	SIGNATURE	
		SIGN	STAMP
3	<p><b>HYSERESIS</b></p> <p>a) The hysteresis test shall begin not more than 15 minutes after the altimeter's initial exposure to the pressure corresponding to the upper limit of the scale error test prescribed in sub par (2a) and while the altimeter is at this pressure, the hysteresis test shall commence. The pressure shall be increased at a rate simulating a decent in altitude at a rate of 5000 to 20000 ft. per minute until within 3000 ft. of the first test point (50% of maximum altitude). The test point shall then be approached at a rate of approximately 3000 ft. per minute.</p> <p>b) The altimeter shall be kept at this pressure for at least 5 minutes, but not more than 15 minutes before the test reading is taken. After the reading has been taken, the pressure shall be increased further, in the same manner as before, until the pressure corresponding to the second test point (40% of Maximum altitude) is reached</p> <p>c) The altimeter shall be kept at this pressure for at least 1 minute, but not more than 10 minutes, before the test reading is taken. After the reading has been taken the pressure shall be increased further, in the same manner as before, until atmospheric pressure is reached. The reading of the altimeter at either of the two test points shall not differ by more than the tolerance specified in Table II from the reading of the altimeter for the corresponding altitude record during the scale error test prescribed in paragraph (2 a).</p>		
4	<p><b>AFTER EFFECT</b></p> <p>a) Not more than 5 minutes after the completion of the hysteresis test prescribed in paragraph (3), the reading of the altimeter (corrected for any change in atmospheric pressure), shall not differ from the original atmospheric pressure reading by more than the tolerance specified in Table II.</p>		
5	<p><b>FRICTION</b></p> <p>a) The altimeter shall be subjected to a steady rate of decrease of pressure of approximately 750 ft. per minute at each altitude listed in table III, the change in reading of the pointers after vibration shall not exceed the corresponding tolerances listed in Table III</p>		

6	<p><b>CASE LEAK</b></p> <p>a) The leakage of the altimeter case, when pressure within it corresponds to an altitude of 18000 ft. shall not change the altimeter reading by more than the tolerances shown in Table II during the interval of 1 minute.</p>		
7	<p><b>BAROMETRIC SCALE ERROR</b></p> <p>At constant atmospheric pressure, the barometric pressure scale shall be set at each of the pressure (falling within its range at adjustment), that are listed in Table IV and shall cause the pointer to indicate the equivalent altitude difference shown in Table IV with a tolerance of 25ft.</p>		
8	<p><b>AUTOMATIC PRESSURE ALTITUDE REPORTING EQUIPMENT AND ATC TRANSPONDER SYSTEM INTEGRATION TEST.</b></p> <p>a) Measure the automatic pressure altitude at the output of the installed ATC Transponder when interrogated on Mode C at a sufficient number of test points to ensure that the altitude reporting equipment, altimeter and ATC Transponder perform their intended functions as installed in the aircraft.</p> <p>b) The difference between the automatic reporting output and the altitude display at the altimeter shall not exceed 125 ft.</p>		
*** End of Static Pressure Inspection Items ***			

**Table I**

Altitude in Feet (ft.)	Equivalent Pressure (Inches of Mercury)	Tolerance (+ Feet)
-1000	31.018	20
0	29.921	20
+ 500	29.385	20
+1000	28.856	20
+1500	28.335	25
+2000	27.821	30
+3000	26.187	30
+4000	25.842	35
+6000	23.978	40
+8000	22.225	60
+10000	20.557	80
+12000	19.029	90
+14000	17.577	100
+16000	16.216	110
+18000	14.942	120
+20000	13.750	130
+22000	12.636	140
+25000	11.104	155
+30000	8.885	180
+35000	7.041	205
+40000	5.538	230
+45000	4.335	255
+50000	3.425	280

**Table II – TEST TOLERANCES**

TEST	TOLERANCE FEET (ft.)
Case Leak Test	100
Hysteresis Test	75
First test point (59% Maximum altitude )	75
Second test point (40% Maximum altitude)	75
After effect test	30

**Table III – ESSURE / ALTITUDE DIFFERENCES**

TEST	TOLERANCE FEET (ft.)
1000	+70
2000	+70
3000	+70
5000	+70
10000	+80
15000	+90
20000	+100
25000	+120
30000	+140
35000	+160
40000	+180
50000	+250

**Table IV – PRESSURE / ALTITUDE DIFFERENCES**

PRESSURE (Inches of HG)	ALTIDE DIFFERENCE FEET (ft.)
28.10	-1727
28.50	+1340
29.00	-863
29.50	+392
29.92	0
30.50	+531
30.90	+894
30.99	-974

Aircraft Static System Test			@ 1000 ft.		± 100 ft	Case Leak At 18000 Feet	Tolerance ±100ft.
Altitude	Scale Error	Scale Toler-ance (±)	Friction Error	Friction Toler-ance (±)	ATC (if used) (±125)		
0		20					
500		20					
1000		20		70			
1500		25					
2000		30		70			
3000		30		70			
5000				70			
6000		40					
8000		60					
10000		80		80			
12000		90					
14000		100					
15000				90			
16000		110					
18000		120					
20000		130		100			
22000		140					
25000		155		120			
30000		180		140			
35000		205		160			
40000		230		180			
45000		255					
50000		280		250			

**RETURN TO SERVICE**

The work recorded above has been carried out in accordance with the requirements of the Civil Aviation Safety Regulation for the time being in force and in that respect the aircraft is considered fit for Release to Service.

Name : \_\_\_\_\_ Place/Date : \_\_\_\_\_

Sign & Stamp : \_\_\_\_\_

	<p style="text-align: center;"><b>ELT (12 Months) Inspection Sheet D04</b>  <u>Instructions</u></p> <ul style="list-style-type: none"> <li>- Each Listed Inspection Item is to be performed in accordance with the AMM and any other applicable publications</li> <li>- This equipment should be inspected within 12 calendar after last inspection</li> <li>- Reference CASR Part 91.207</li> </ul>
---	--

Aircraft Registration :	PK-	TTIS:	
Aircraft Type :		TCIS:	
Aircraft Serial Number :		DATE:	
ELT PN:		ELT SN:	
ELT BATTERY PN:		ELT BATTERY SN:	

No.	TASK	SIGNATURE	
		SIGN	STAMP
1	<p><b>EMERGENCY LOCATOR TRANSMITTER</b></p> <p>Check for correct installation, perform visual inspection for cracks and corrosion and general condition. Inspect magnesium components for corrosion.</p> <p>Check the ELT and mount for improper installation; Wiring and conduits for improper routing, insecure mounting, and obvious defects; Bonding and shielding for improper installation and poor condition; and Antenna, including trailing antenna, for poor condition, insecure mounting, and improper operation.</p>		
2	<p><b>ELT BATTERY</b></p> <p>Check ELT battery expiry date and record _____</p> <p>Replace ELT battery (if required).</p> <p>Part Number OFF _____ SN OFF _____</p> <p>Part Number ON _____ SN ON _____</p> <p>Batch / GRN number _____</p> <p>New Battery Expiry Date _____</p>		
3	Inspect operation of controls and crash sensor.		
4	Check the presence of a sufficient signal radiated from the antenna		
*** End of ELT 12 Months Inspection Items ***			

**RETURN TO SERVICE**

The work recorded above has been carried out in accordance with the requirements of the Civil Aviation Safety Regulation for the time being in force and in that respect the aircraft is consider fit for Release to Service.

Name : \_\_\_\_\_ Place/Date : \_\_\_\_\_

Sign & Stamp : \_\_\_\_\_