



**PT. SMART CAKRAWALA AVIATION**

**WORK ORDER**

**Form: SCA/MTC/030**

|                                          |             |                    |
|------------------------------------------|-------------|--------------------|
| Subject :                                | No.         | WO/012-SNB/XI/2022 |
| <b>Engine and Propeller Installation</b> | Date        | 8 Nov 2022         |
|                                          | A/C Reg.    | PK-SNB MSN 1015    |
| Reference :                              | Prepared By | TS                 |
| MP Pilatus PC-6                          | Checked By  | CI                 |
| AMM Pilatus PC-6                         | Approved By | TM                 |

To : Engineer In Charge

**Description :**

1. Perform Engine and Propeller Installation
2. Make an entry in Maintenance Log.
3. Return the Completed Work Order and Form to PPC.

#If any finding, please close the routine card, and transferred to inspection card.

**Additional Work :**

|                      |                                                              |                                      |
|----------------------|--------------------------------------------------------------|--------------------------------------|
| Compliance Statement | Sign & Date<br>Company Lic. No.:<br><br>(Engineer In Charge) | Signature<br><br>(Technical Manager) |
|----------------------|--------------------------------------------------------------|--------------------------------------|

## AIRCRAFT CHECK WORK SUMMARY

(Form: SCA/MTC/051)

|                     |                    |                                   |                          |
|---------------------|--------------------|-----------------------------------|--------------------------|
| DATE OF ISSUED      | JO/WO #            | TYPE OF MAINTENANCE               | DATE OF ACCOMPLISHED     |
| 8 Nov 2022          | WO/012-SNB/XI/2022 | Engine and Propeller Installation |                          |
| A/C Type            |                    | Mfg. Serial Number                | A/C Registration         |
| PILATUS PORTER PC-6 |                    | 1015                              | PK-SNB                   |
| AIRCRAFT DATA       |                    |                                   |                          |
| Subject             | Pos #              | Serial Number (SN)                | TTSN/TCSN                |
| Engine              | #1                 | PCE-51153                         | TSN: 18599:8H CSN: 19230 |
|                     | #2                 | -                                 | TSO: 0 CSO: 0            |
| Propeller/Rotor     | #1                 | FY4093                            | TSN: 739:56H TSO: 0      |
|                     | #2                 | -                                 |                          |
| Landing Gear        | NLG                |                                   |                          |
|                     | LH MLG             |                                   |                          |
|                     | RH MLG             |                                   |                          |

### PACKAGE COVERED

| No | Subject                             | Qty | Remark |
|----|-------------------------------------|-----|--------|
| 1  | Non-Routine Card                    | -   |        |
| 2  | Inspection Card                     | -   |        |
| 3  | Work Order                          | 1   |        |
| 4  | Summary Inspection List             | 1   |        |
| 5  | Material and Tool List              | -   |        |
| 6  | Escalation form                     | -   |        |
| 7  | CRS (SMI / Unscheduled Maintenance) | 1   |        |

### INSPECTION CARD (IC) LIST (Finding during maintenance)

| No     | Taskcard Ref | Subject | Status |       | Name/<br>Sign & Stamp |
|--------|--------------|---------|--------|-------|-----------------------|
|        |              |         | Open   | Close |                       |
| IC-001 |              |         |        |       |                       |
| IC-002 |              |         |        |       |                       |
| IC-003 |              |         |        |       |                       |
| IC-004 |              |         |        |       |                       |
| IC-005 |              |         |        |       |                       |
| IC-006 |              |         |        |       |                       |

|               |  |  |  |  |  |
|---------------|--|--|--|--|--|
| <u>IC-007</u> |  |  |  |  |  |
| <u>IC-008</u> |  |  |  |  |  |
| <u>IC-009</u> |  |  |  |  |  |
| <u>IC-010</u> |  |  |  |  |  |
| <u>IC-011</u> |  |  |  |  |  |
| <u>IC-012</u> |  |  |  |  |  |
| <u>IC-013</u> |  |  |  |  |  |
| <u>IC-014</u> |  |  |  |  |  |
| <u>IC-015</u> |  |  |  |  |  |

Prepared by :  
Technical Support



Hani

Checked by :  
Chief Maintenance



Dodit

Verified by :  
Chief Inspector



Yanuar

Approved by :  
Technical Manager



Istiono



**SUMMARY INSPECTION ITEMS**  
**(Form: SCA/MTC/050)**

WO Ref: WO/012-SNB/XI/2022

| NO. | TASK CARD NO. | DESCRIPTION            | DATE | EST MHR | NAME | STAMP |
|-----|---------------|------------------------|------|---------|------|-------|
| 1   | APPENDIX      | PROPELLER INSTALLATION |      |         |      |       |
| 2   | APPENDIX      | ENGINE INSTALLATION    |      |         |      |       |
|     |               |                        |      |         |      |       |
|     |               |                        |      |         |      |       |



PT. SMART CAKRAWALA AVIATION

# CERTIFICATE RETURN TO SERVICE

## SCHEDULED MAINTENANCE INSPECTION

### (CRS-SMI)

| A/C TYPE                                                                                              | : PILATUS PORTER PC-6               |             |            | TTSN | :    |
|-------------------------------------------------------------------------------------------------------|-------------------------------------|-------------|------------|------|------|
| A/C REG                                                                                               | : PK-SNB                            |             |            | TCSN | :    |
| MSN                                                                                                   | : 1015                              |             |            | DATE | :    |
| TYPE OF INSPECTION                                                                                    | : ENGINE AND PROPELLER INSTALLATION |             |            |      |      |
| DUE AT                                                                                                | : N/A                               |             |            |      |      |
| REFF                                                                                                  | : MP PILATUS PC-6                   |             |            |      |      |
| EXCEPTION                                                                                             |                                     |             |            |      |      |
| AUTHORIZED PERSON                                                                                     |                                     |             |            |      |      |
| I hereby certify that this aircraft has been maintained accordance with CASR and Maintenance Program. |                                     |             |            |      |      |
| Aircraft safe and airworthy for flight                                                                |                                     |             |            |      |      |
| NAME                                                                                                  | CAT                                 | AMEL/OTR NO | SIGN&STAMP |      | DATE |
|                                                                                                       | AIRFRAME & POWER PLANT              |             |            |      |      |
|                                                                                                       | EIRA                                |             |            |      |      |
| THE NEXT DUE TYPE OF INSPECTION :                                                                     |                                     |             |            |      |      |
| DUE AT :                                                                                              |                                     |             |            |      |      |



**INSPECTION CARD**  
(Form: SCA/MTC/048)

TECHNICAL  
DEPARTMENT

|                |             |               |                    |         |
|----------------|-------------|---------------|--------------------|---------|
| 1. CARD #      | 2. JO/WO #  | 3. ORIGINATOR | 4. CARD REF        | 5. DATE |
|                |             |               |                    |         |
| 6. A/C REG/MSN | 7. A/C TYPE | 8. TRADE      | 12. VENDOR ORDER # |         |
|                |             |               |                    |         |
| 9. ZONE        | 10. STA     | 11. MTC TYPE  |                    |         |
|                |             |               |                    |         |

|                                                                               |               |            |
|-------------------------------------------------------------------------------|---------------|------------|
| 13. DESCRIPTION/DEFECT-IF FINDING OF CPCP INSPECTION, PLEASE COMPLETE SET. 20 | 14<br>PPC/ENG | 15<br>DATE |
|                                                                               |               |            |

|                                                                                                |                                           |                                                 |            |
|------------------------------------------------------------------------------------------------|-------------------------------------------|-------------------------------------------------|------------|
| 16. CORRECTIVE ACTION                                                                          | 17<br>MECH                                | 18<br>ENG. LIC                                  | 19<br>DATE |
|                                                                                                |                                           |                                                 |            |
| Performed at A/C TT : ..... A/C TC /LDG : .....                                                |                                           |                                                 |            |
| 20. CORROSION INFORMATION                                                                      |                                           |                                                 |            |
| LOCATION                                                                                       | CAUSE OF DAMAGE                           |                                                 |            |
|                                                                                                | <input type="checkbox"/> Environment      |                                                 |            |
|                                                                                                | <input type="checkbox"/> Internal Leakage |                                                 |            |
| CORROSION <input type="checkbox"/> Isolated <input type="checkbox"/> Widespread                | <input type="checkbox"/> Chemical Spill   |                                                 |            |
| CORROSION LVL <input type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 | <input type="checkbox"/> LAV/Galley Spill |                                                 |            |
| PROPOSED ACTION <input type="checkbox"/> Doublers                                              | <input type="checkbox"/> Blocked Drain    |                                                 |            |
|                                                                                                | <input type="checkbox"/> Others           | <input type="checkbox"/> Wet Insulation Blanket |            |
|                                                                                                | <input type="checkbox"/> Other            |                                                 |            |
| 21. If the defect is RII, Please Sign this card finally by RII Inspector                       | INSP                                      | DATE                                            |            |
| NOTICE OF INSPECTOR                                                                            |                                           |                                                 |            |

|                    |         |     |           |     |        |      |
|--------------------|---------|-----|-----------|-----|--------|------|
| 22. PARTS REQUIRED |         |     |           |     |        |      |
| PART DESCRIPTION   | PART NO | QTY | SERIAL NO |     | STATUS |      |
|                    |         |     | ON        | OFF | CLOSE  | OPEN |
|                    |         |     |           |     |        |      |
|                    |         |     |           |     |        |      |
|                    |         |     |           |     |        |      |
|                    |         |     |           |     |        |      |

|                    |                  |                       |        |
|--------------------|------------------|-----------------------|--------|
| 23. TOOLS REQUIRED |                  |                       |        |
| DESCRIPTION        | PART NO. / MODEL | NEXT CALIBRATION DATE | STATUS |
|                    |                  |                       |        |
|                    |                  |                       |        |
|                    |                  |                       |        |
|                    |                  |                       |        |



# MAINTENANCE PROGRAM PILATUS PORTER PC6

## Appendix – Engine Installation

| Ref. AMM Pilatus Porter PC6 Chapter 71-00-00,<br>P&WC Maintenance Manual Model PT6A-27 Manual Part No. 3013242 Chapter 72-00-00 |                                                                                                                                                                                                                                                                                                                                                   |              |           |
|---------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-----------|
| <b>ENGINE INSTALLATION SHEET</b>                                                                                                |                                                                                                                                                                                                                                                                                                                                                   |              |           |
| Date :                                                                                                                          |                                                                                                                                                                                                                                                                                                                                                   | Engine P/N : | 3015000   |
| Aircraft Registration :                                                                                                         |                                                                                                                                                                                                                                                                                                                                                   | Engine S/N : | PCE-51153 |
| Aircraft Type :                                                                                                                 |                                                                                                                                                                                                                                                                                                                                                   | TSN :        | 18599:8H  |
| Aircraft Total Hours :                                                                                                          |                                                                                                                                                                                                                                                                                                                                                   | TSO :        | 19230     |
| Aircraft Total Cycle :                                                                                                          |                                                                                                                                                                                                                                                                                                                                                   | CSN :        | 0         |
| Work Order Number :                                                                                                             |                                                                                                                                                                                                                                                                                                                                                   | CSO :        | 0         |
| NO                                                                                                                              | TASK                                                                                                                                                                                                                                                                                                                                              |              | SIGNATURE |
|                                                                                                                                 |                                                                                                                                                                                                                                                                                                                                                   |              | SIGN      |
| <b>Job Set Up</b>                                                                                                               |                                                                                                                                                                                                                                                                                                                                                   |              |           |
| A                                                                                                                               | Make inventory records P/N and S/N of the engine and it's accessories from the engine that removed. Fill out into the form no ASI/MD-50 Engine Change- Major Component Inventory Records.                                                                                                                                                         |              |           |
| <b>Install the following item of Engine Accessories on the Engine before proceeding to install on the airplane:</b>             |                                                                                                                                                                                                                                                                                                                                                   |              |           |
| A                                                                                                                               | <b>CAUTION: MAKE SURE THAT ALL BLANKS AND COVERS REMOVED FROM THE REPLACEMENT ENGINE ARE INSTALLED TO ALL OPENINGS ON THE REMOVED ENGINE</b>                                                                                                                                                                                                      |              |           |
|                                                                                                                                 | <b>Oil Drain Valve (Ref. Fig. 409)</b><br>1. Remove the blank from the opening.<br>2. Install a new O-ring (4) to the oil drain valve (5).<br>3. Install the drain valve (5) with the lock pin (2).<br>4. Safety the lockpin (2) with a new cotter pin.<br>5. Install the bolt (1).                                                               |              |           |
| B                                                                                                                               | <b>Oil Temperature Sensor (Ref. Fig. 409)</b><br>1. Remove the blank from the opening.<br>2. Install a new O-ring (11) to the oil temperature sensor.<br>3. Install the oil temperature sensor (10).                                                                                                                                              |              |           |
|                                                                                                                                 | <b>Engine Breather Elbow (Ref. Fig. 409)</b><br>1. Remove the blank from the opening.<br>2. Install a new O-ring (8) to the elbow (9).<br>3. Install the elbow (9) with the bolts (6) and washers (7).<br>4. Torque the bolts (6) to between 3.4 and 3.9 Nm (30 and 35 lbf in.).<br>5. Safety the bolts (6) with lockwire (Material No. P02-001). |              |           |



# MAINTENANCE PROGRAM

## PILATUS PORTER PC6

### Appendix – Engine Installation

| NO | TASK                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | SIGNATURE |       |
|----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-------|
|    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | SIGN      | STAMP |
| D  | <p><b>Control Levers (Ref. Fig. 405)</b></p> <p>1. Idle Control Lever:</p> <ol style="list-style-type: none"><li>Put the lever (9) in position on the idle control unit.</li><li>Install the washer (10) and nut (11), then tighten the nut (11) with your hand</li><li>Install the bolt (6), control rod end (5), spacers (7) and (4), washer (3) and nut (2).</li><li>Torque the nut (2) to between 1.3 and 2.0 Nm (12 and 18 lbf in.).</li><li>Safety the nut (2) with a new cotter pin (1).</li><li>Torque the nut (11) to between 1.3 and 2.0 Nm (12 and 18 lbf in.).</li><li>Safety the nut (11) with a new cotter pin (8).</li></ol> <p>2. Power Control Input Lever</p> <p><b>CAUTION:</b> WHEN YOU INSTALL THE LEVER (18) IT MUST BE IN LINE WITH THE FOLLOWER LEVER ON THE SAME SHAFT OF THE CAM BOX.</p> <ol style="list-style-type: none"><li>Install the lever (18) to the splined shaft.</li><li>Install the bolt (17), the washer (19) and the nut (20). Safety the nut (20) with a new cotter pin (21).</li></ol> |           |       |
| E  | <p><b>Engine Driven Fuel Pump (Ref. Fig. 410)</b></p> <ol style="list-style-type: none"><li>Remove the blank from the opening.</li><li>Install a new gasket (8).</li><li>Install the fuel pump (7), washers (5) and nuts (6).</li><li>Torque the nuts (6) to between 8,5 and 9,6 Nm (75 and 85 lbf in.).</li></ol>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |           |       |
| F  | <p><b>Gas Generator and Propeller Tachometer Generators (Ref. Fig. 410)</b></p> <ol style="list-style-type: none"><li>Remove the blank from the opening.</li><li>Install a new gasket (2).</li><li>Install the generator (1), washers (3) and nuts (4).</li><li>Torque the nuts (4) to between 8,5 and 9,6 Nm (75 and 85 lbf in.).</li></ol>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |           |       |
| G  | <p><b>Torque Indicating System (Ref. Fig. 411, Sheets 1 and 2)</b></p> <ol style="list-style-type: none"><li>Install a new O-ring (1).</li><li>Install the adapter (8).</li><li>Remove the bottom RH nut (6) from the propeller tachometer generator.</li><li>Install the P-clip (4) and torque transducer (3).</li><li>Install the nut (6).</li><li>Torque the nut (6) to between 8,5 and 9,6 Nm (75 and 85 lbf in.).</li><li>Install the torque pressure pipe (2).</li><li>Install the case reference pressure hose (7).</li></ol>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |           |       |
| H  | <p><b>Propeller Overspeed Governor (Ref. Fig. 412)</b></p> <ol style="list-style-type: none"><li>Install a new gasket (4) on the replacement engine.</li><li>Install the governor with the washers (1) and nuts (2).</li><li>Torque the nuts (2) to between 19,2 and 21,5 Nm (170 and 190 lbf in.).</li></ol>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |           |       |



# MAINTENANCE PROGRAM

## PILATUS PORTER PC6

### Appendix – Engine Installation

| NO | TASK                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | SIGNATURE |       |
|----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-------|
|    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | SIGN      | STAMP |
| I  | <b>Drain Line Adapter, QAD Adapter (if applicable) and Starter-Generator (Ref. Fig. 413)</b><br><ol style="list-style-type: none"><li>1. Install the drain adapter (7).</li><li>2. Install a new gasket (1).</li><li>3. If applicable, install the QAD adapter (2) with the washers (3) and nuts (4).</li><li>4. Install the starter-generator (Ref. 24-31-11) but connect the electrical cables after you install the engine (Ref. Para. 7.H.(1))</li></ol>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |           |       |
| J  | <b>Harness (Ref. Fig. 414)</b><br><ol style="list-style-type: none"><li>1. If applicable, install the propeller de-icer unit (Ref. 30-60-01, Page Block 401).</li><li>2. If necessary, replace the heat insulating tape installed on the harness between the engine flanges A and C.</li><li>3. Put the harness assembly in position on the engine.</li><li>4. Install the P-clips to secure the harness.</li><li>5. Remove the identity marks and connect the ITT indication leads to the T5 terminal block.</li><li>6. If applicable, remove the identity marks and connect the propeller de-icer leads to the de-icer unit terminal block.</li><li>7. Connect the electrical plugs at the:<ol style="list-style-type: none"><li>i. chip detector.</li><li>ii. propeller tachometer generator.</li><li>iii. torque pressure transducer.</li></ol></li><li>8. Remove the two thrust bearing cover attaching nuts.</li><li>9. Install the low pitch warning switch mounting bracket and warning switch on to the mounting studs.</li><li>10. Install the warning switch linkage block on to mounting stud on the propeller reversing lever.</li><li>11. Install the washer and nut to secure the warning switch linkage block, then tighten the nut with your hand. Make sure that the block is free to turn on the stud.</li><li>12. Safety the nut with a new cotter pin.</li></ol> |           |       |
| K  | <b>Propeller Governor Maximum Stop Screw (Ref. Fig. 405)</b><br><ol style="list-style-type: none"><li>1. Check the maximum stop screw (35) on the propeller governor. If the screw is shorter than the stop screw on the removed engine, move the screws as follows:<br/><b>NOTE:</b> The long stop screw is used to give the propeller speed of 2000 rpm used on B2H4 aircraft.<ol style="list-style-type: none"><li>a. On the removed engine:<ol style="list-style-type: none"><li>i. Loosen the locknut.</li><li>ii. Remove the stop screw, at the same time count the number of turns necessary to remove the stop screw.</li><li>iii. Make a record of the number of turns.</li></ol></li><li>b. Move the short stop screw from the replacement engine to the removed engine.</li><li>c. Install the long stop screw on the propeller governor of the replacement engine with the same number of turns as recorded at (a) (iii).</li><li>d. Tighten the stop screw locknut.</li></ol></li></ol>                                                                                                                                                                                                                                                                                                                                                                                  |           |       |

| NO                  | TASK                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | SIGNATURE |       |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-------|
|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | SIGN      | STAMP |
| L                   | <p><b>Inner Bulkheads (Ref. Fig. 415)</b></p> <ol style="list-style-type: none"> <li>1. Put the forward bulkheads (1) and (13) in position.</li> <li>2. Install the bolts (2), washers (3) and nuts (4).</li> <li>3. Install the bolts (5), washers (10) and nuts (11).</li> <li>4. Install the harness slot filler plate on to the engine forward bulkhead.</li> <li>5. Use caulking putty (Material No. P08-001) to seal the gaps between the harness and the bulkhead.</li> <li>6. Put the rear bulkheads (6) and (12) in position.</li> <li>7. Install the bolts (7), washers (8) and nuts (9).</li> </ol>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |           |       |
| <b>Installation</b> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |           |       |
| A                   | <p><b>Engine Mounting Ring (Ref. Fig. 408)</b></p> <ol style="list-style-type: none"> <li>1. Position the mounting ring on the engine to the rear of the attachment points.<br/><b>NOTE:</b> Make sure that the support strut attachment lugs on the mounting ring are to the rear.</li> <li>2. Install the engine lifting sling (Ref. P&amp;WC EMM 72-00-00, SERVICING).<br/><b>CAUTION:</b> THE BUSHES THAT ATTACH THE SHOCKMOUNT TO THE MOUNTING FRAME BOLT MUST BE INSTALLED. THE BUSH MUST HAVE THE THICK FLANGE TO THE REAR. IF THE BUSH IS INCORRECTLY INSTALLED, THE ENGINE WILL NOT ALIGN CORRECTLY.</li> <li>3. Install the gaskets (7), shockmounts (10), washers (6) and bolts (5).</li> <li>4. Torque the bolts (5) to between 31.0 and 34.0 Nm (275 and 300 lbf in.).</li> <li>5. Safety the bolts in pairs with lockwire (Material No. P02-001).</li> <li>6. Lubricate the shanks of the mounting ring attachment bolts (8).</li> <li>7. Put the mounting ring in position.</li> <li>8. Install the bolts (8), washers (9) and (12) and nuts (11).</li> <li>9. Torque the nuts (11) to between 55.0 and 60.0 Nm (486 and 531 lb in.).</li> </ol> |           |       |
| B                   | <p><b>Install the Engine (Ref. Fig. 408)</b></p> <ol style="list-style-type: none"> <li>1. Lift the engine in position.</li> <li>2. Install the bolts (16) and washers (13).</li> <li>3. Torque the bolts (16) to between 46,0 and 51,0 Nm (407 and 450 lb in.).</li> <li>4. Safety the bolts (16) with locking wire (Material No. P02-001).</li> </ol>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |           |       |

| NO | TASK                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | SIGNATURE |       |
|----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-------|
|    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | SIGN      | STAMP |
| C  | <p><b>Support Struts (Ref. Fig. 408)</b></p> <ol style="list-style-type: none"> <li>1. Put the rear bulkhead over the engine.</li> <li>2. Loosely install 10 bolts (five each side) to attach the upper and lower half of the bulkhead together.</li> <li>3. Put the support struts in position through the holes in the engine rear bulkhead.</li> <li>4. Install the bolt (1), washer (2) and nut (3).</li> <li>5. Torque the nuts (3) to between 10,5 and 12,5 Nm (95 and 110 lb in.).</li> <li>6. Safety the nuts with new cotter pins (4).</li> <li>7. Make sure the bonded shim (18) is securely attached to the structure.</li> <li>8. If the nuts (15) are self-locking nuts:           <ol style="list-style-type: none"> <li>i. Install the bolt (19) washer (17) and nut (15). When you do this measure the rundown torque of the nut (15).</li> <li>ii. Torque the nuts (15) to between 51 and 56 Nm (450 and 500 lb in.) plus the rundown torque.</li> </ol> </li> <li>9. If the nuts (15) are castellated nuts:           <ol style="list-style-type: none"> <li>i. Install the bolt (19), washer (17) and nut (15).</li> <li>ii. Torque the nuts (15) to between 51 and 56 Nm (450 and 500 lb in.).</li> <li>iii. Safety the nuts (15) with new cotter pins (14).</li> </ol> </li> <li>10. Remove the lifting sling from the engine</li> </ol> |           |       |
| D  | <p><b>Connect the Engine Bulkheads (Ref. Fig. 407)</b></p> <ol style="list-style-type: none"> <li>1. Install the bolts (6) and washers (7) to attach the upper half of the engine rear bulkhead.</li> <li>2. Tighten the bolts (4) and washers (3) that attach the support strut seal plates (5) and seals (2).</li> </ol>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |           |       |
| E  | <p><b>Case Drains and P3 Air Bleed (Ref. Fig. 402)</b></p> <ol style="list-style-type: none"> <li>1. Connect the gas generator case rear drain hose (8) at the rear drain valve.</li> <li>2. Connect the gas generator case forward drain hose (1) at the engine forward bulkhead.</li> <li>3. Connect the gas generator case forward drain pipe (7).</li> <li>4. Install the gasket (6) to the mounting boss on the top of the gas generator case.</li> <li>5. Put the adapter in position and install the four bolts (4).</li> <li>6. Connect the P3 bleed air hose (2) to the adapter (5).</li> <li>7. Install the P-clip (3) on the P3 bleed air hose (2) and engine forward bulkhead.</li> <li>8. Safety the hose to the lower LH side of the engine mounting ring with a cable tie.</li> </ol>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |           |       |

| NO | TASK                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | SIGNATURE |       |
|----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-------|
|    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | SIGN      | STAMP |
| F  | <p><b>Fuel Tubes (Ref. Fig. 404, Sheets 1 and 2)</b></p> <ol style="list-style-type: none"> <li>1. Install a new O-ring (11) on the adapter (12).</li> <li>2. Install the adapter to the starting flow control unit.</li> <li>3. Set the adapter to the position noted at 4. E. (10).</li> <li>4. Hold the adapter and then tighten the adapter locknut.</li> <li>5. Connect the fuel dump hose (14) to the adapter (12).</li> <li>6. Install and tighten the worm-drive clamp (13).</li> <li>7. Connect fuel bleed return hose (10) to starting flow control unit.</li> <li>8. Install a new O-ring (1) to the adapter (2).</li> <li>9. Install the adapter (2) to the oil fuel heater.</li> <li>10. (10) Connect the fuel supply hose (3) to the adapter (2).</li> <li>11. Connect the drain tube (8) to the LP fuel pump.</li> <li>12. Install a new O-ring (5) to the adapter (6).</li> <li>13. Install the adapter (6) to the HP fuel pump.</li> <li>14. Connect the drain tube (7) to the adapter (6).</li> <li>15. Connect the inlet hose (4) to the LP fuel pump.</li> <li>16. Connect outlet hose (9) to the LP fuel pump.</li> </ol> |           |       |
| G  | <p><b>Oil Tubes (Ref. Fig. 403)</b></p> <ol style="list-style-type: none"> <li>1. Connect the starter generator drain hose (Ref. Fig. 413):             <ol style="list-style-type: none"> <li>i. Connect the drain hose (5) to the drain adapter (7) below the starter generator drive.</li> <li>ii. Install and tighten the clamp (6).</li> </ol> </li> <li>2. Connect the engine breather hose (3) to the breather elbow.</li> </ol> <p>Install and tighten the clamp (2).</p> <ol style="list-style-type: none"> <li>3. Connect the oil cooler return hose (1) to the adapter on top of the accessory gearbox.</li> <li>4. Connect the engine oil cooler supply hose (7) to the connector on the scavenging pump.</li> <li>5. Install a new O-ring (4) to the adapter (5) at the RH of the accessory gearbox.</li> <li>6. Install the adapter (5).</li> <li>7. Connect the oil pressure transducer hose (6) to the adapter (5).</li> </ol>                                                                                                                                                                                                 |           |       |
| H  | <p><b>Electrical Connectors (Ref. Fig. 401)</b></p> <ol style="list-style-type: none"> <li>1. Connect the electrical cables (1) to the starter-generator.</li> <li>2. Connect the electrical plug (8) to the oil temperature sensor.</li> <li>3. Connect the electrical plug (7) to the FCU sense line heater.</li> <li>4. Connect the electrical plug (5) to the gas generator tachometer generator.</li> <li>5. Connect the electrical plug (2) to the ignition unit.</li> <li>6. Connect the electrical plug (9) at the RH of the front face of the engine rear bulkhead.</li> <li>7. If the propeller de-icing system is installed:             <ol style="list-style-type: none"> <li>i. Install electrical plug (10) at the RH front face of the engine rear bulkhead.</li> </ol> </li> <li>8. Install the earth leads (6) to engine bulkhead.</li> </ol> <p>Connect bonding lead (3) to engine data plate securing bolt (4).</p>                                                                                                                                                                                                        |           |       |

| NO | TASK                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | SIGNATURE                                                                                                                                                                 |       |
|----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|
|    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | SIGN                                                                                                                                                                      | STAMP |
| I  | <p><b>Connect the Propeller Control Cable (Ref. Fig. 406)</b></p> <ol style="list-style-type: none"> <li>1. Insert the cable through the hole in the engine rear bulkhead.</li> <li>2. Install the two grommets to the cable.</li> <li>3. Insert the cable through the hole in the forward bulkhead.</li> <li>4. Position the cable on the engine.</li> <li>5. Press the grommets in the holes of the bulkhead.</li> <li>6. Put the support bracket (9) in position.</li> <li>7. Install the bolts (12), washers (10) and nuts (11).</li> <li>8. Put the cable in position on the support bracket (9).</li> <li>9. Install the top plate (15) with the bolts (16), spring washers (14) and nuts (13).</li> </ol>                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                           |       |
| J  | <p><b>Connect the Controls (Ref. Fig. 405)</b></p> <ol style="list-style-type: none"> <li>1. Insert the cable through the hole in the engine rear bulkhead.</li> <li>2. Install the two grommets to the cable.</li> <li>3. Insert the cable through the hole in the forward bulkhead.</li> <li>4. Position the cable on the engine.</li> <li>5. Press the grommets in the holes of the bulkhead.</li> <li>6. Put the support bracket (9) in position.</li> <li>7. Install the bolts (12), washers (10) and nuts (11).</li> <li>8. Put the cable in position on the support bracket (9).</li> <li>9. Install the top plate (15) with the bolts (16), spring washers (14) and nuts (13).</li> </ol>                                                                                                                                                                                                                                                                                                                                                                                                            | <div style="border: 1px solid black; padding: 2px; display: inline-block;">RII :</div><br><div style="display: inline-block; vertical-align: top;">Sign &amp; Stamp</div> |       |
| K  | <p><b>Connect the Controls (Ref. Fig. 405)</b></p> <ol style="list-style-type: none"> <li><b>1. Idle Control:</b> <ol style="list-style-type: none"> <li>i. Put the rod (15) in position and then install the bolt (16), washer (14) and nut (13).</li> <li>ii. Torque the nut (13) to between 1,3 and 2,0 Nm (12 and 18 lbf in.).</li> <li>iii. Safety the nut with a new cotter pin.</li> </ol> </li> <li><b>2. Power Control:</b> <ol style="list-style-type: none"> <li>i. Put the rod end (25) in position and then install the bolt (26), washer (24) and nut (23).</li> <li>ii. Torque the nut (23) to between 1,3 and 2,0 Nm (12 and 18 lbf in.).</li> <li>iii. Safety the nut with a new cotter pin (22).</li> </ol> </li> <li><b>3. Propeller Control:</b> <ol style="list-style-type: none"> <li>i. Put the control rod (31) in position and then install the bolt (34), washer (33), spacer (32), washer (29) and nut (26).</li> <li>ii. Torque the nut (26) to between 1,3 and 2,0 Nm (12 and 18 lbf in.).</li> <li>iii. Safety the nut (26) with a new cotter pin (22).</li> </ol> </li> </ol> | <div style="border: 1px solid black; padding: 2px; display: inline-block;">RII :</div><br><div style="display: inline-block; vertical-align: top;">Sign &amp; Stamp</div> |       |



# MAINTENANCE PROGRAM

## PILATUS PORTER PC6

### Appendix – Engine Installation

| NO                  | TASK                                                                              | SIGNATURE |       |
|---------------------|-----------------------------------------------------------------------------------|-----------|-------|
|                     |                                                                                   | SIGN      | STAMP |
| <b>Job Close Up</b> |                                                                                   |           |       |
| A                   | 1. Adjust the engine controls.                                                    | RII:      |       |
|                     | 2. Install the exhaust stubs.                                                     |           |       |
|                     | 3. Install the propeller.                                                         | RII:      |       |
|                     | 4. If applicable, install the oil cooler.                                         |           |       |
|                     | 5. Fill the engine oil system.                                                    |           |       |
|                     | 6. If installed, remove the aircraft tail stand and lower aircraft tail.          |           |       |
|                     | 7. Make sure that the work area is clean and clear of tools and other items.      |           |       |
|                     | 8. Do a fuel system de-preservation.                                              |           |       |
|                     | 9. Remove the engine compressor intake cover.                                     |           |       |
|                     | 10. Install the engine cowlings.                                                  |           |       |
|                     | 11. Connect the aircraft battery,                                                 |           |       |
|                     | 12. Do an engine ground run and fill out Engine Ground Run Sheet.                 |           |       |
| B                   | Make an appropriate entry in Work Order or Aircraft Flight Maintenance Log (AFML) |           |       |

| PERSONNEL PARTICIPATING IN THIS INSPECTION |          |           |                |
|--------------------------------------------|----------|-----------|----------------|
| NAME                                       | POSITION | SIGNATURE | LICENSE NUMBER |
|                                            |          |           |                |
|                                            |          |           |                |
|                                            |          |           |                |
|                                            |          |           |                |



# MAINTENANCE PROGRAM

## PILATUS PORTER PC6

### Appendix – Engine Installation

#### RETURN TO SERVICE

The work recorded above has been carried out in accordance with the requirements of the Civil Aviation Safety Regulation for the time being in force and in that respect the aircraft is consider fit for Release to Service.


Name : \_\_\_\_\_ Name of RII : \_\_\_\_\_

Signature : \_\_\_\_\_ Signature : \_\_\_\_\_

Stamp : \_\_\_\_\_ Stamp : \_\_\_\_\_


Place/Date : \_\_\_\_\_ Place/Date : \_\_\_\_\_

**PILATUS**  
**PC-6**  
**MAINTENANCE MANUAL**




Powerplant - Removal / Installation - Electrical Connections  
Figure 401 (Sheet 1 of 2)

**PILATUS**  
**PC-6**  
**MAINTENANCE MANUAL**




Powerplant - Removal / Installation - Electrical Connections  
Figure 401 (Sheet 2 of 2)

**PILATUS**  
**PC-6**  
**MAINTENANCE MANUAL**




Powerplant - Removal / Installation - Case Drains and P3 Air Bleed  
 Figure 402

**PILATUS**  
**PC-6**  
MAINTENANCE MANUAL



Powerplant - Removal / Installation - Oil Tubes  
Figure 403


**PILATUS**  
**PC-6**  
**MAINTENANCE MANUAL**



Powerplant - Removal / Installation - Fuel Tubes  
Figure 404 (Sheet 1 of 2)

6214


**PILATUS**  
**PC-6**  
MAINTENANCE MANUAL



601


Powerplant - Removal / Installation - Fuel Tubes  
Figure 404 (Sheet 2 of 2)

**PILATUS**  
**PC-6**  
MAINTENANCE MANUAL






Powerplant - Removal / Installation - Control Connections and Levers  
Figure 405

**PILATUS**  
**PC-6**  
MAINTENANCE MANUAL



Powerplant - Removal / Installation - Control Cable Connections and Support Brackets  
Figure 406


**PILATUS**  
**PC-6**  
MAINTENANCE MANUAL



Powerplant - Removal / Installation - Engine Bulkheads  
Figure 407





6240

**PILATUS**  
**PC-6**  
**MAINTENANCE MANUAL**



**Powerplant - Removal / Installation - Engine Mounts and Support Struts**  
**Figure 408**


**PILATUS**  
**PC-6**  
**MAINTENANCE MANUAL**



Powerplant - Removal / Installation - Oil Temperature Sensor, Breather and Drain Valve  
 Figure 409

625


**PILATUS**  
**PC-6**  
**MAINTENANCE MANUAL**



©11



Powerplant - Removal / Installation - Engine Driven Fuel Pump and Gas Generator and Tachometer Generator  
Figure 410

**PILATUS**  
**PC-6**  
**MAINTENANCE MANUAL**



Powerplant - Removal / Installation - Torque System (Aircraft from MSN 825)  
Figure 411 (Sheet 2 of 2)



**PILATUS**  
**PC-6**  
**MAINTENANCE MANUAL**



©12




Powerplant - Removal / Installation - Propeller Overspeed Governor  
Figure 412

**PILATUS**  
**PC-6**  
**MAINTENANCE MANUAL**



Powerplant - Removal / Installation - Starter-Generator, QAD Adapter (if installed) and Pad Drain Adapter  
Figure 413


**PILATUS**  
**PC-6**  
**MAINTENANCE MANUAL**



6250

Powerplant - Removal / Installation - Electrical Harness (Aircraft from MSN 824)  
 Figure 414 (Sheet 2 of 2)

**PILATUS**  
**PC-6**  
**MAINTENANCE MANUAL**



Powerplant - Removal / Installation - Engine Inner Bulkheads  
Figure 415



# MAINTENANCE PROGRAM PILATUS PORTER PC6

## Appendix – Engine Installation

|  |                                                                                                    |
|--|----------------------------------------------------------------------------------------------------|
|  | ENGINE GROUND RUN CHECK SHEET - PT6A-27 ENGINE<br>WITH FOUR BLADE PROPELLER (HARTZELL STC SA377CH) |
|  |                                                                                                    |

|                       |                         |                                 |       |
|-----------------------|-------------------------|---------------------------------|-------|
| WORK ORDER NO.        | :                       |                                 |       |
| Aircraft Registration | Aircraft Total Hours    |                                 |       |
| Aircraft Serial No.   | Aircraft Total Landings |                                 |       |
| Engine Serial No.     | Engine TSN / TSO        |                                 |       |
| Propeller Serial No   | Propeller TSN / TSO     |                                 |       |
| Ambient Temp          | °C                      | FBP (Field Barometric Pressure) | In.Hg |
| Date                  |                         | Time                            |       |
| Mechanic / Engineer   | Authorized Engineer     |                                 |       |
| Reason For Ground Run |                         |                                 |       |

|                               |   |   |   |   |   |   |   |    |    |    |    |    |    |
|-------------------------------|---|---|---|---|---|---|---|----|----|----|----|----|----|
| Checks to be carried out. No: | 1 | 2 | 4 | 5 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
|-------------------------------|---|---|---|---|---|---|---|----|----|----|----|----|----|

### Engine Ground Run Check Frequency

| Check Number             | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
|--------------------------|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|
| Each 100 / Yearly        | x | x |   | x |   |   | x | x |   |    | x  | x  | x  | x  | x  |
| Each 200                 |   |   |   |   |   |   |   |   | x |    |    |    |    |    |    |
| Pre-Complete Overhaul    | x | x | x | x |   | x | x | x | x | x  | x  | x  | x  | x  | x  |
| After Short Term Storage |   |   |   |   |   |   |   |   |   |    |    |    |    |    | x  |
| After Long Term Storage  | x | x | x | x |   | x | x | x | x | x  | x  | x  | x  | x  | x  |

In additional the following check must be carried out after Installation, Repair and Adjustment of any of the following components.

| Check Number               | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
|----------------------------|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|
| Engine Installation        | x | x | x | x | x | x | x | x | x | x  | x  | x  | x  | x  | x  |
| Propeller Installation     |   | x | x | x | x |   |   |   | x |    |    |    |    |    |    |
| Fuel Control Unit          | x |   |   |   | x | x | x | x |   | x  | x  |    |    |    |    |
| HP Fuel Pump               |   |   |   |   |   | x | x |   |   |    |    |    |    |    |    |
| Fuel Nozzle                |   |   |   |   |   | x | x |   |   |    |    |    |    |    |    |
| Starting Flow Control      | x |   |   |   | x |   | x | x |   |    |    |    |    |    |    |
| Emer Fuel Control Actuator |   |   |   |   |   |   |   |   |   |    | x  |    |    |    |    |
| Prop Governor              | x |   | x | x | x |   | x | x |   |    |    |    |    |    |    |
| Prop Overspeed Governor    |   |   |   |   |   |   |   |   |   | x  |    |    |    |    |    |
| Compressor Bleed Valve     |   |   |   |   |   | x | x |   |   |    |    |    |    |    |    |
| Engine Controls            | x |   |   | x | x |   |   | x | x |    |    |    |    |    |    |
| Low Pitch Warning Switch   |   |   |   | x |   |   |   |   |   |    |    |    |    |    |    |
| Suction Components         |   |   |   |   |   |   |   |   |   |    |    | x  |    |    |    |



# MAINTENANCE PROGRAM PILATUS PORTER PC6

## Appendix – Engine Installation

Use this sheet's to record engine run result, use in conjunction with task cards.

| NO. | CHECK                                                        | TARGET                          | ACTUAL |
|-----|--------------------------------------------------------------|---------------------------------|--------|
|     | <b>ENGINE START</b><br>ITT (Troubleshoot If More Than 925°C) | Max. 1090 °C                    | °C     |
|     | Cabin Heat                                                   | OFF                             | OK?    |
| 1   | Low Idle (Minimum Governing) Speed                           | 51 - 53 % Ng                    | % Ng   |
|     | Fuel Pressure / Boost Pump OFF                               | Light out or 25 ± 5 psi         | OK?    |
|     | ITT                                                          |                                 | °C     |
|     | Oil Pressure                                                 |                                 | psi    |
|     | Oil Temperature                                              |                                 | °C     |
| 2   | Propeller Governor                                           |                                 |        |
|     | Maximum Np                                                   | 1980 - 2000 rpm (90.0 - 90.9 %) | rpm    |
|     | Py Disconnected                                              |                                 | % Ng   |
|     | Py Connected                                                 |                                 | % Ng   |
|     | Difference                                                   | Maximum 0.3% Ng                 | %      |
|     | Airbleed Link at Minimum                                     | 1900 - 1950 rpm (86.4 - 88.6 %) | rpm    |
|     | Aircraft with SB 161:                                        |                                 |        |
|     | Propeller Control Lever at Minimum                           | 1880 - 1900 rpm (85.5 - 86.4 %) | rpm    |
| 3   | Propeller Fine Pitch Setting (High Idle)                     |                                 |        |
|     | Target Torque                                                |                                 | psi    |
|     | Power Lever to Give Np                                       | 1694 rpm (77 %)                 | rpm    |
|     | Basic High Idle                                              | 68 - 72% Ng                     | % Ng   |
| 4   | Propeller Low Pitch Warning                                  |                                 |        |
|     | PCL from Reverse to Detent                                   | Light OFF                       |        |
|     |                                                              | 1 to 2 mm before Detent         | mm     |
| 5   | Minimum Pitch in Flight                                      |                                 |        |
|     | Ng                                                           | 67 - 73 %                       | % Ng   |
|     | Np                                                           | 1800 - 1950 rpm (81.8 - 88.6 %) | rpm    |
|     | Torque                                                       | 4 - 7 psi                       | psi    |
| 6   | FCU Maximum Governing Speed (Ng)<br>(Trim stop deployed)     | 97.1 % Ng                       | % Ng   |



# MAINTENANCE PROGRAM PILATUS PORTER PC6

## Appendix – Engine Installation

| NO.               | CHECK                                                                                                                                                | TARGET                                                                                                                                                | ACTUAL                                            |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------|
| 7                 | <b>Engine Performance</b><br>Target Torque Pressure<br>Fuel flow (Actual minus 23 lb / hr<br>or 3.4 gal / hr)<br>Target Ng<br>Maximum ITT            | Ref: AMM 71-00-00<br><br><br><br><br>psi<br>lb / hr<br>% Ng<br>0C                                                                                     | psi<br>lb / hr<br>% Ng<br>0C                      |
| 8                 | <b>Reverse Power Setting</b><br><br>Np<br>Torque                                                                                                     | 1880 - 1925 rpm (85.5 - 87.5 %)<br><br>psi                                                                                                            | rpm<br>psi                                        |
| 9                 | <b>Propeller Overspeed Governor</b><br><br>Test Lever Selected to:<br><br>TEST<br>NORMAL                                                             | <br><br>1880 - 1920 rpm (85.5 - 87.3 %)<br><br>1980 - 2000 rpm (90.0 - 90.9 %)                                                                        | <br><br>rpm<br>rpm                                |
| 10                | <b>Acceleration</b><br><br>64 % – 90 % Ng<br><br><b>Deceleration</b><br><br>85% to 60% Ng or low idle<br>speed(Whichever<br>comes first)             | 2.5 – 4 secs<br><br><br>Maximum 6-12 sec<br><br>(Dependent upon altitude)                                                                             | <br><br>secs<br><br>secs<br><br>altitude<br>(kFt) |
|                   | <b>Manual Override (MOR)</b><br>(Aircraft with SB 164)<br><br>Use Toggle Switch In Small Increment<br>(REF. to WARNINGS and CAUTIONS in<br>Check 11) | <br><br>Increase to 15% above Idle<br>(Max Increase less than 4 %<br>per Second)<br><br>Decrease To Idle<br>(Max Decrease less Than 4%<br>per Second) | <br><br>OK?<br><br>OK?                            |
| 12                | Oil Pressure                                                                                                                                         | 80 -100 psi                                                                                                                                           | psi                                               |
| 13                | Generator (Ref. 24-30-00)                                                                                                                            | Online by 60% Ng                                                                                                                                      | % Ng                                              |
| 14                | Suction (High Idle)                                                                                                                                  | 4.5 – 5.2 in. Hg                                                                                                                                      | in. Hg                                            |
| 15                | Engine Rundown Time After Stop                                                                                                                       | MIN 30 secs                                                                                                                                           | secs                                              |
| <b>Additional</b> |                                                                                                                                                      |                                                                                                                                                       |                                                   |
|                   | Generator Check (High Idle Under Load)                                                                                                               | 27.75 – 28.25 VDC                                                                                                                                     | VDC                                               |
|                   | After Engine Run                                                                                                                                     |                                                                                                                                                       |                                                   |
|                   | Check Eng. For Signs of Fuel/Oil/Air Leaks                                                                                                           | NO LEAKS FOUND                                                                                                                                        | OK?                                               |
|                   | Safety All Screws, Bolts, Locknuts as Req.                                                                                                           |                                                                                                                                                       | OK?                                               |



# MAINTENANCE PROGRAM PILATUS PORTER PC6

## Appendix – Propeller Installation

Ref. AMM Pilatus Porter PC6 Chapter 61-10-00,

### PROPELLER INSTALLATION SHEET

| Date                  | :    |                    | Propeller P/N     | :         | D4N00163SKD        |
|-----------------------|------|--------------------|-------------------|-----------|--------------------|
| Aircraft Registration | :    | PK-SNB             | Propeller S/N     | :         | FY4093             |
| Aircraft Type         | :    | PILATUS PC6, B2-H4 | TSN               | :         | 739:56H            |
| Aircraft Total Hours  | :    | 476:14             | TSO               | :         | 0                  |
| Aircraft Total Cycle  | :    | 580                | Work Order Number | :         | WO-012-SNB-XI-2022 |
| NO                    | TASK |                    |                   | SIGNATURE |                    |
|                       |      |                    |                   | SIGN      | STAMP              |

#### Job Set Up

|   |                                                                                          |  |  |
|---|------------------------------------------------------------------------------------------|--|--|
| 1 | Do Engine Run Ground Sheet before Propeller installation, fill out FormNo. <b>XXXXXX</b> |  |  |
| 2 | Ensure airplane electrical power is OFF.                                                 |  |  |

#### Installation (Ref. Fig. 401)

|   |                                                                                                                                                                                                                                                           |                      |  |  |
|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|--|--|
| 1 | (1) Attach the puller (16) and pull the slip ring fully forward to touch the rear face of the propeller bulkhead.                                                                                                                                         | RII:<br>Sign & Stamp |  |  |
|   | (2) Install a new O-ring (15) on the propeller shaft.                                                                                                                                                                                                     | RII:<br>Sign & Stamp |  |  |
|   | (3) Install the sling and put the propeller in position on the engine flange.                                                                                                                                                                             | RII:<br>Sign & Stamp |  |  |
|   | (4) Lubricate the bolts (7) with grease (Material No. P04-009).                                                                                                                                                                                           | RII:<br>Sign & Stamp |  |  |
|   | <b>CAUTION:</b><br>MAKE SURE THAT THE CHAMFERED SIDE OF THE WASHER FACES THE BOLT HEAD.                                                                                                                                                                   |                      |  |  |
| 1 | (5) Install the attachment bolts (7) and washers (8), with the chamfered side of the washer next to the bolt head.                                                                                                                                        | RII:<br>Sign & Stamp |  |  |
|   | (6) Torque the bolts in three steps as follows:<br>a) To 54 Nm (480 lbf in.), (Ref. Fig. 402, Sequence A).<br>b) To 108 Nm (960 lbf in.), (Ref Fig. 402, Sequence A).<br>c) To between 136 and 142 Nm (1200 and 1260 lbf in.), (Ref. Fig402, Sequence B). | RII:<br>Sign & Stamp |  |  |
|   |                                                                                                                                                                                                                                                           |                      |  |  |



# MAINTENANCE PROGRAM

## PILATUS PORTER PC6

### Appendix – Propeller Installation

| NO                  | TASK                                                                                                                                                                                                                                 | SIGNATURE                   |       |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|-------|
|                     |                                                                                                                                                                                                                                      | SIGN                        | STAMP |
|                     | (7) Safety the bolts with lockwire (Material No. P02-001).                                                                                                                                                                           | <b>RII:</b><br>Sign & Stamp |       |
|                     | (8) Remove the sling and puller.                                                                                                                                                                                                     |                             |       |
|                     | (9) Put the carbon block (9) in position.                                                                                                                                                                                            | <b>RII:</b><br>Sign & Stamp |       |
|                     | (10) Put the reversing lever (12) in position.                                                                                                                                                                                       | <b>RII:</b><br>Sign & Stamp |       |
|                     | (11) Put the low pitch switch control rod in position.                                                                                                                                                                               | <b>RII:</b><br>Sign & Stamp |       |
|                     | (12) Install the nut (5) and washer (6).                                                                                                                                                                                             | <b>RII:</b><br>Sign & Stamp |       |
|                     | (13) Safety the nut with a new cotter pin (4).                                                                                                                                                                                       | <b>RII:</b><br>Sign & Stamp |       |
|                     | (14) Install the pin (3) and washer (11).                                                                                                                                                                                            | <b>RII:</b><br>Sign & Stamp |       |
|                     | (15) Safety the pin with a new cotter pin (10).                                                                                                                                                                                      | <b>RII:</b><br>Sign & Stamp |       |
|                     | (16) Install the bolt (2), bush (15), washer (14) and nut (13).                                                                                                                                                                      | <b>RII:</b><br>Sign & Stamp |       |
|                     | (17) Install the bolt (2), bush (15), washer (14) and nut (13).                                                                                                                                                                      | <b>RII:</b><br>Sign & Stamp |       |
|                     | (18) Safety the nut with a new cotter pin (1).                                                                                                                                                                                       | <b>RII:</b><br>Sign & Stamp |       |
|                     | (19) Make sure the side clearance between the beta-ring and the carbon block (9) is between 0,03 and 0,25 mm (0.001 and 0.01 in). If necessary, remove material from, or replace, the carbon block (9) to get the correct clearance. | <b>RII:</b><br>Sign & Stamp |       |
| <b>Job Close Up</b> |                                                                                                                                                                                                                                      |                             |       |
| 1                   | (1) Install the spinner dome to the bulkhead assembly. Align the marks on the spinner with the marks on the bulkhead.                                                                                                                | <b>RII:</b><br>Sign & Stamp |       |



# MAINTENANCE PROGRAM

## PILATUS PORTER PC6

### Appendix – Propeller Installation


| NO | TASK                                                                                                                        | SIGNATURE |       |
|----|-----------------------------------------------------------------------------------------------------------------------------|-----------|-------|
|    |                                                                                                                             | SIGN      | STAMP |
|    | <b>NOTE:</b> The spinner assembly (plate, bulkhead and dome) is balanced as a unit. The components are not interchangeable. |           |       |
|    | (2) Do a balance check.                                                                                                     |           |       |
|    | (3) Do a ground run.                                                                                                        |           |       |
|    | (4) Check for oil leaks from the propeller, - No leaks are acceptable.                                                      |           |       |
|    | (5) Make sure that the work area is clean and clear of tools and other items.                                               |           |       |
|    | (6) Install the engine cowls PT1 and PB1.                                                                                   |           |       |
| 2  | Make an appropriate entry in Work Order or Aircraft Flight Maintenance Log (AFML)                                           |           |       |

| PERSONNEL PARTICIPATING IN THIS INSPECTION |          |           |                |
|--------------------------------------------|----------|-----------|----------------|
| NAME                                       | POSITION | SIGNATURE | LICENSE NUMBER |
|                                            |          |           |                |
|                                            |          |           |                |
|                                            |          |           |                |
|                                            |          |           |                |
|                                            |          |           |                |


### RETURN TO SERVICE

The work recorded above has been carried out in accordance with the requirements of the Civil Aviation Safety Regulation for the time being in force and in that respect the aircraft is considered fit for Release to Service.


|            |   |                                  |             |   |                                  |
|------------|---|----------------------------------|-------------|---|----------------------------------|
| Name       | : | _____<br>_____<br>_____<br>_____ | Name of RII | : | _____<br>_____<br>_____<br>_____ |
| Signature  | : | _____<br>_____<br>_____<br>_____ | Signature   | : | _____<br>_____<br>_____<br>_____ |
| Stamp      | : | _____<br>_____<br>_____<br>_____ | Stamp       | : | _____<br>_____<br>_____<br>_____ |
| Place/Date | : | _____<br>_____<br>_____<br>_____ | Place/Date  | : | _____<br>_____<br>_____<br>_____ |



**PILATUS**  
**PC-6**  
**MAINTENANCE MANUAL**



**SEQUENCE A**



**SEQUENCE B**

Propeller - Bolt Tightening Sequence  
Figure 402



# MAINTENANCE PROGRAM PILATUS PORTER PC6

## Appendix – Propeller Installation

|  |                                                                                                    |
|--|----------------------------------------------------------------------------------------------------|
|  | ENGINE GROUND RUN CHECK SHEET - PT6A-27 ENGINE<br>WITH FOUR BLADE PROPELLER (HARTZELL STC SA377CH) |
|  |                                                                                                    |

|                       |                         |                                 |       |
|-----------------------|-------------------------|---------------------------------|-------|
| WORK ORDER NO.        | :                       |                                 |       |
| Aircraft Registration | Aircraft Total Hours    |                                 |       |
| Aircraft Serial No.   | Aircraft Total Landings |                                 |       |
| Engine Serial No.     | Engine TSN / TSO        |                                 |       |
| Propeller Serial No   | Propeller TSN / TSO     |                                 |       |
| Ambient Temp          | °C                      | FBP (Field Barometric Pressure) | In.Hg |
| Date                  |                         | Time                            |       |
| Mechanic / Engineer   | Authorized Engineer     |                                 |       |
| Reason For Ground Run |                         |                                 |       |

|                               |   |   |   |   |   |   |   |    |    |    |    |    |    |
|-------------------------------|---|---|---|---|---|---|---|----|----|----|----|----|----|
| Checks to be carried out. No: | 1 | 2 | 4 | 5 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
|-------------------------------|---|---|---|---|---|---|---|----|----|----|----|----|----|

### Engine Ground Run Check Frequency

| Check Number             | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
|--------------------------|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|
| Each 100 / Yearly        | X | X |   | X |   |   | X | X |   |    | X  | X  | X  | X  | X  |
| Each 200                 |   |   |   |   |   |   |   |   | X |    |    |    |    |    |    |
| Pre-Complete Overhaul    | X | X | X | X |   | X | X | X | X | X  | X  | X  | X  | X  | X  |
| After Short Term Storage |   |   |   |   |   |   |   |   |   |    |    |    |    |    | X  |
| After Long Term Storage  | X | X | X | X |   | X | X | X | X | X  | X  | X  | X  | X  | X  |

In additional the following check must be carried out after Installation, Repair and Adjustment of any of the following components.

| Check Number               | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
|----------------------------|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|
| Engine Installation        | X | X | X | X | X | X | X | X | X | X  | X  | X  | X  | X  | X  |
| Propeller Installation     |   | X | X | X | X |   |   |   | X |    |    |    |    |    |    |
| Fuel Control Unit          | X |   |   |   | X | X | X | X |   | X  | X  |    |    |    |    |
| HP Fuel Pump               |   |   |   |   |   | X | X |   |   |    |    |    |    |    |    |
| Fuel Nozzle                |   |   |   |   |   | X | X |   |   |    |    |    |    |    |    |
| Starting Flow Control      | X |   |   |   | X |   | X | X |   |    |    |    |    |    |    |
| Emer Fuel Control Actuator |   |   |   |   |   |   |   |   |   |    |    | X  |    |    |    |
| Prop Governor              | X |   | X | X | X |   | X | X |   |    |    |    |    |    |    |
| Prop Overspeed Governor    |   |   |   |   |   |   |   |   |   |    | X  |    |    |    |    |
| Compressor Bleed Valve     |   |   |   |   |   | X | X |   |   |    |    |    |    |    |    |
| Engine Controls            | X |   |   | X | X |   |   | X | X |    |    |    |    |    |    |
| Low Pitch Warning Switch   |   |   |   | X |   |   |   |   |   |    |    |    |    |    |    |
| Suction Components         |   |   |   |   |   |   |   |   |   |    |    |    | X  |    |    |



# MAINTENANCE PROGRAM

## PILATUS PORTER PC6

### Appendix – Propeller Installation

Use this sheet's to record engine run result, use in conjunction with task cards.

| NO. | CHECK                                                        | TARGET                          | ACTUAL |
|-----|--------------------------------------------------------------|---------------------------------|--------|
|     | <b>ENGINE START</b><br>ITT (Troubleshoot If More Than 925°C) | Max. 1090 °C                    | °C     |
|     | Cabin Heat                                                   | OFF                             | OK?    |
| 1   | Low Idle (Minimum Governing) Speed                           | 51 - 53 % Ng                    | % Ng   |
|     | Fuel Pressure / Boost Pump OFF                               | Light out or 25 ± 5 psi         | OK?    |
|     | ITT                                                          |                                 | °C     |
|     | Oil Pressure                                                 |                                 | psi    |
|     | Oil Temperature                                              |                                 | °C     |
| 2   | Propeller Governor                                           |                                 |        |
|     | Maximum Np                                                   | 1980 - 2000 rpm (90.0 - 90.9 %) | rpm    |
|     | Py Disconnected                                              |                                 | % Ng   |
|     | Py Connected                                                 |                                 | % Ng   |
|     | Difference                                                   | Maximum 0.3% Ng                 | %      |
|     | Airbleed Link at Minimum                                     | 1900 - 1950 rpm (86.4 - 88.6 %) | rpm    |
|     | Aircraft with SB 161:                                        |                                 |        |
|     | Propeller Control Lever at Minimum                           | 1880 - 1900 rpm (85.5 - 86.4 %) | rpm    |
| 3   | Propeller Fine Pitch Setting (High Idle)                     |                                 |        |
|     | Target Torque                                                |                                 | psi    |
|     | Power Lever to Give Np                                       | 1694 rpm (77 %)                 | rpm    |
|     | Basic High Idle                                              | 68 - 72% Ng                     | % Ng   |
| 4   | Propeller Low Pitch Warning                                  |                                 |        |
|     | PCL from Reverse to Detent                                   | Light OFF                       |        |
|     |                                                              | 1 to 2 mm before Detent         | mm     |
| 5   | Minimum Pitch in Flight                                      |                                 |        |
|     | Ng                                                           | 67 - 73 %                       | % Ng   |
|     | Np                                                           | 1800 - 1950 rpm (81.8 - 88.6 %) | rpm    |
|     | Torque                                                       | 4 - 7 psi                       | psi    |
| 6   | FCU Maximum Governing Speed (Ng)<br>(Trim stop deployed)     | 97.1 % Ng                       | % Ng   |



# MAINTENANCE PROGRAM PILATUS PORTER PC6

## Appendix – Propeller Installation

| NO.               | CHECK                                                                                                                                                              | TARGET                                                                                                                                    | ACTUAL                                         |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|
| 7                 | <b>Engine Performance</b><br><b>Target Torque Pressure</b><br><b>Fuel flow (Actual minus 23 lb / hr or 3.4 gal / hr)</b><br><b>Target Ng</b><br><b>Maximum ITT</b> | Ref: AMM 71-00-00<br><br><br><br><br>                                                                                                     | psi<br><br>lb / hr<br>% Ng<br>0C               |
| 8                 | <b>Reverse Power Setting</b><br><br>Np<br>Torque                                                                                                                   | 1880 - 1925 rpm (85.5 - 87.5 %)                                                                                                           | <br><br>rpm<br>psi                             |
| 9                 | <b>Propeller Overspeed Governor</b><br><br><b>Test Lever Selected to:</b><br><br>TEST<br>NORMAL                                                                    | <br><br>1880 - 1920 rpm (85.5 - 87.3 %)<br><br>1980 - 2000 rpm (90.0 - 90.9 %)                                                            | <br><br>rpm<br>rpm                             |
| 10                | <b>Acceleration</b><br><br>64 % – 90 % Ng<br><br><b>Deceleration</b><br><br>85% to 60% Ng or low idle speed(Whichever comes first)                                 | <br><br>2.5 – 4 secs<br><br>Maximum 6-12 sec<br><br>(Dependent upon altitude)                                                             | <br><br>secs<br><br>secs<br><br>altitude (kFt) |
|                   | <b>Manual Override (MOR)</b><br>(Aircraft with SB 164)<br><br>Use Toggle Switch In Small Increment (REF. to <b>WARNINGS</b> and <b>CAUTIONS</b> in Check 11)       | <br><br>Increase to 15% above Idle (Max Increase less than 4 % per Second)<br><br>Decrease To Idle (Max Decrease less Than 4% per Second) | <br><br>OK?<br><br>OK?                         |
| 12                | Oil Pressure                                                                                                                                                       | 80 -100 psi                                                                                                                               | psi                                            |
| 13                | Generator (Ref. 24-30-00)                                                                                                                                          | Online by 60% Ng                                                                                                                          | % Ng                                           |
| 14                | Suction (High Idle)                                                                                                                                                | 4.5 – 5.2 in. Hg                                                                                                                          | in. Hg                                         |
| 15                | Engine Rundown Time After Stop                                                                                                                                     | MIN 30 secs                                                                                                                               | secs                                           |
| <b>Additional</b> |                                                                                                                                                                    |                                                                                                                                           |                                                |
|                   | Generator Check (High Idle Under Load)                                                                                                                             | 27.75 – 28.25 VDC                                                                                                                         | VDC                                            |
|                   | After Engine Run                                                                                                                                                   |                                                                                                                                           |                                                |
|                   | Check Eng. For Signs of Fuel/Oil/Air Leaks                                                                                                                         | NO LEAKS FOUND                                                                                                                            | OK?                                            |
|                   | Safety All Screws, Bolts, Locknuts as Req.                                                                                                                         |                                                                                                                                           | OK?                                            |



Aircraft Registration: **PK-SNB**

WO# Nr: **WO/012-SNB/XI/2022**



## **Additional Work Sheet Engine and Propeller Installation**

## Parts Used Sheet

## Special Tool Used



Aircraft Registration: **PK-SNB**

WO# Nr: **WO/012-SNB/XI/2022**



# **Additional Work Sheet**

## **Engine and Propeller**

### **Installation**

## Parts Used Sheet

## Part Used