

AIRCRAFT CHECK WORK SUMMARY
(Form: SCA/MTC/051)

DATE OF ISSUED		JO/WO #		TYPE OF MAINTENANCE		DATE OF ACCOMPLISHED	
4 SEPT 2022		WO/100-SNM/IX/2022		Inspection 100 Hours			
A/C Type		Mfg. Serial Number		A/C Registration			
C208		C208-00655		PK-SNM			
AIRCRAFT DATA							
Subject		Pos #		Serial Number (SN)		TTSN/TCSN	
Engine		#1		PCE-PC2316			
		#2		-			
Propeller/Rotor		#1		190085			
		#2		-			
Landing Gear		NLG					
		LH MLG					
		RH MLG					
PACKAGE COVERED							
No	Subject			Qty	Remark		
1	Non-Routine Card			-			
2	Inspection Card			1			
3	Work Order			1			
4	Summary Inspection List			1			
5	Material and Tool List			-			
6	Escalation form			-			
7	CRS (SMI / Unscheduled Maintenance)			1			
INSPECTION CARD (IC) LIST (Finding during maintenance)							
No	Taskcard Ref	Subject	Status		Name/ Sign & Stamp		
			Open	Close			
<u>IC-001</u>							
<u>IC-002</u>							
<u>IC-003</u>							
<u>IC-004</u>							
<u>IC-005</u>							
<u>IC-006</u>							

<u>IC-007</u>					
<u>IC-008</u>					
<u>IC-009</u>					
<u>IC-010</u>					
<u>IC-011</u>					
<u>IC-012</u>					
<u>IC-013</u>					
<u>IC-014</u>					
<u>IC-015</u>					

Prepared by :
Technical Support

Checked by :
Chief Maintenance

Verified by :
Chief Inspector

Approved by :
Technical Manager


.....
Dwi M.


.....
Dodit


.....
Yanuar


.....
Istiono



SUMMARY INSPECTION ITEMS
(Form: SCA/MTC/050)

WO Ref: WO/0100-SNM/IX/2022

NO.	TASK CARD NO.	DESCRIPTION	DATE	EST MHR	NAME	STAMP
1	B02	PT6A-114A ENGINE GROUND RUN PERFORMANCE				
2	CHAPTER 44	ENGINE PT6A-114A 100 HOURS/MINOR INSPECTION				
3	Form SCA/MTC/0 23	EMERGENCY EQUIPMENT CHECKLIST				



PT. SMART CAKRAWALA AVIATION

CERTIFICATE RETURN TO SERVICE

SCHEDULED MAINTENANCE INSPECTION (CRS-SMI)

A/C TYPE : CESSNA 208	TTSN :
A/C REG : PK-SNM	TCSN :
MSN : C208-00655	DATE :

TYPE OF INSPECTION	: INSPECTION 100 HOURS
DUE AT	: 3654 HOURS
REF	: MP C208/C208B REV. 12

EXCEPTION

AUTHORIZED PERSON

I hereby certify that this aircraft has been maintained accordance with CASR and Maintenance Program.
Aircraft safe and airworthy for flight

NAME	CAT	AMEL/OTR NO	SIGN&STAMP	DATE
	AIRFRAME & POWER PLANT			
	EIRA			

THE NEXT DUE TYPE OF INSPECTION	:
DUE AT	:

Form: SCA/MTC/049

	INSPECTION CARD (Form: SCA/MTC/ 048)	TECHNICAL DEPARTMENT
---	---	---------------------------------

1. CARD #	2. JO/WO #	3. ORIGINATOR	4. CARD REF	5. DATE
6. A/C REG/MSN	7. A/C TYPE	8. TRADE	12. VENDOR ORDER #	
9. ZONE	10. STA	11. MTC TYPE		

13. DESCRIPTION/DEFECT-IF FINDING OF CPCP INSPECTION, PLEASE COMPLETE SET. 20	14 PPC/ENG	15 DATE

16. CORRECTIVE ACTION	17 MECH	18 ENG. LIC	19 DATE
Performed at A/C TT : A/C TC /LDG :			

20. CORROSION INFORMATION					
LOCATION	CAUSE OF DAMAGE				
	☐ Environment				
	☐ Internal Leakage				
CORROSION ☐ Isolated ☐ Widespread	☐ Chemical Spill				
CORROSION LVL ☐ 1 ☐ 2 ☐ 3	☐ LAV/Galley Spill				
PROPOSED ACTION ☐ Doublers	☐ Blocked Drain				
☐ Others	☐ Wet Insulation Blanket				
.....	☐ Other				
21. If the defect is RII, Please Sign this card finally by RII Inspector				INSP	DATE
NOTICE OF INSPECTOR					

22. PARTS REQUIRED						
PART DESCRIPTION	PART NO	QTY	SERIAL NO		STATUS	
			ON	OFF	CLOSE	OPEN

23. TOOLS REQUIRED			
DESCRIPTION	PART NO. / MODEL	NEXT CALIBRATION DATE	STATUS



MAINTENANCE PROGRAM CESSNA C208/C208B

Appendix B02 – PT6A-114A Engine Run Performance Sheet

Reg. Mark : PK - SNM

WO/FML No. : WO/0100-SNM/IX/2022

PRE – INSPECTION	
Location	
Date	
Cycle	
Filed Barometric	
OAT	
Altitude	

POST – INSPECTION	
Location	
Date	
Cycle	
Filed Barometric	
OAT	
Altitude	

PRE – INSPECTION		
	Target	Actual
Tq		
Np		
ITT	°C	°C
Ng	%	%
Wf		
Oil Press		°C
Oil Temp		°C
Start Temp		°C

POST – INSPECTION		
	Target	Actual
Tq		
Np		
ITT	°C	°C
Ng	%	%
Wf		
Oil Press		°C
Oil Temp		°C
Start Temp		°C

Engine Run Up Checks							
Inertial ☐	EPL ☐	OVG ☐	Stby Alt ☐	BOV ☐	Brake ☐	Randomn ☐	
NOTE: 1. Brake system at Torque 1500 ft-lbs. 3. EPL check can't exceed 4% Ng per second. 5. Low idle at 52.5 – 53.5% 40Amps. 2. Inertial Separator at Torque 400 ft-lbs. 4. Standby Alt at 80% Ng. 6. High idle at 64 - 66% Ng 40Amps.							

Engine Performance Target Table Cessna C208

OAT (°C)	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
Tq (ft.lbs)	1865	1865	1865	1865	1865	1865	1865	1865	1865	1865	1865	1865	1865	1865	1865
Np	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
ITT (°C)	772	775	778	780	785	790	793	795	797	800	800	800	802	805	810
Ng (%)	98.5	98.5	99	99	99.1	99.2	99.4	99.5	99.5	100	100	100.2	100.5	100.7	100.9
WF (PPH)	450	450	450	450	450	450	450	450	450	450	450	450	448	448	446

Note:

1. Make sure that inertial separator in normal condition, no bleed air extracted from the engine and air condition OFF.
2. This table only applies to altitude 0-500 feet MSL. For higher altitude, refer to EMM 72-00-00.
3. Max fuel flow is 465 lb/hr fuel flow is not more than 15 lbs/hr higher than the value shown in table.
4. If parameters are outside the target performance table to EMM chapter 71-00-00.

REMARKS:

PERFORMED BY			
Name	Sign & Stamp	Date	Location



MAINTENANCE PROGRAM CESSNA C208/C208B

Chapter 44 – Engine PT6A-114A 100 Hours/Minor Inspection

Reg. Mark	:	PK - SNM	Date	:	
MSN	:	C208-00655	Station	:	
TSN / CSN	:		WO No.	:	WO/0100-SNM/IX/2022

ITEM CODE NO.	ZONE	TASK	SIGNATURE	
			SIGN	STAMP
E710001	130	Do a check of the FCU manual override system for static operation.		
E710003	130	Do a compressor performance recovery wash.		
E710004	130	Inspect all accessible connections, clamps and brackets for attachment. Inspect accessible lockwire and safety cable for security and installation.		
E710005	130	Inspect of wear, chafing, cracks and corrosion for tubing, wiring, control linkage, hose assemblies. NOTE: Visually inspect insulated air tubes for signs of swelling, cracking, bulging of rubber sheath material. Refer to repair section and SB1687 . Replace as necessary.		
E710006	130	Examine linkages. Pay particular attention to rear linkage cam box, fuel control unit arm, telescopic rod and rod end fittings. Disconnect rod ends and clean using solvent (PWC11-027) or (PWC11-031). Lubricate with light grease (PWC04-001) after engine external wash. Examine rod end for corrosion, roughness in rotation, side play and radial play. After lubrication reinstall rod ends and torque to specified value (Ref 76-10-00). Check free movement of linkage.		
E710007	130	Inspect attachment and linkages, air, oil and fuel lines (Ref. 73-10-07/-08). NOTE: Visually inspect insulated air tubes for signs of swelling, cracking, bulging of rubber sheath material. Refer to repair section and SB1687 . Replace as necessary.		
E710011	130	Performed Deceleration Check		
E720001	130	Do a visual inspection of the engine exhaust duct welds.		
E720002	130	Do a visual inspection of the engine exhaust duct for cracks.		
E720003	130	External surfaces, and fireseal mount ring brackets for cracks, distortion, and corrosion of gas generator case (Ref. 72-30-04).		

Chapter 44 – Engine PT6A-114A 100 Hours/Minor Inspection

ITEM CODE NO.	ZONE	TASK	SIGNATURE	
			SIGN	STAMP
E722001	130	Do a visual inspection of the air inlet screen.		
E722004	130	Cracks and attachment of brackets and seals of fireseal mount rings. (Ref. 72-30-01/-02)		
E723000	130	Do a visual inspection with a mirror or a borescope inspection of the First-stage Compressor Rotor and the inlet case for corrosion		
E731002	130	Do a visual inspection of the fuel pump (in-situ inspection only) for installation and leakage		
E731003	130	Check oil-to-fuel heater installation		
E731014	130	Check starting flow control/flow divider for installation and leaks.		
E731015	130	Check outlet filter for foreign matter or distortion (Ref. 73-10-02). (CLEANING / REPLACEMENT) P/N OFF: _____ P/N ON: _____		
E731006	130	Check drain valve for installation and leaks		
E731008	130	Do a visual inspection of the P3 filter and drain valve.		
E731018	130	Clean or replace the P3 filter based on condition, service experience or environment. Note: If corrossions are found, replace filter.		
E732001	130	Check FCU for installation, linkages and pneumatic tubes.		
E732002	130	Examine the FCU for bearing wash-out, shown by blue dye (grease and fuel mixed) at FCU vent.		
E792002	130	Oil filter elements and secondary screen (coarse hat-type screen attached to the inner end of the filter).		
E792003	130	Examine the forward oil transfer elbow installation on the Flange A. Make sure that the bolts tighten correctly		
*** End of Engine PT6A-114A 100 Hours Inspection Items ***				



MAINTENANCE PROGRAM CESSNA C208/C208B

Chapter 44 – Engine PT6A-114A 100 Hours/Minor Inspection

PERSONNEL PARTICIPATING IN THIS INSPECTION			
NAME	POSITION	SIGNATURE	LICENSE NUMBER

RETURN TO SERVICE

The work recorded above has been carried out in accordance with the requirements of the Civil Aviation Safety Regulation for the time being in force and in that respect the aircraft is considered fit for Release to Service.

Name : _____ Stamp : _____
Signature : _____ Place/Date : _____



EMERGENCY EQUIPMENT LIST INSPECTION & MONITOR

**PT. SMART CAKRAWALA
AVIATION
DEPARTMENT TEKNIK
Form: SCA/MTC/023**

DATE :	A/C REG : PK-SNM
A/C TYPE : C208	CHECKER : SIGN:

No.	Description	P/N	S/N	Next Insp.	Remarks
1	Pilot Life Vest				
2	Co-Pilot Life Vest				
3	Pax Life Vest				
4	Pax Life Vest				
5	Pax Life Vest				
6	Pax Life Vest				
7	Pax Life Vest				
8	Pax Life Vest				
9	Pax Life Vest				
10	Pax Life Vest				
11	Pax Life Vest				
12	Pax Life Vest				
13	Firt Aid Kit				
14	Crash Axe Installed				
15	Fire Extinguisher				
16	Life Raft (If Installed)				
17	Survival Kit (If Installed)				
OTHERS					



WO# Nr: WO/0100-SNM/IX/2022

Parts Used Sheet

1

Special Tool Used

[illegible]



Aircraft Registration: **PK-SNM**

WO# Nr: WO/0100-SNM/IX/2022

Parts Used Sheet

4

[illegible]